

PTFE Fortified, Tackifier, Rust Inhibited, UV Tracer

A lithium soap thickened, light viscosity, synthetic hydrocarbon grease. For the lubrication of cams, sliding surfaces, small gear trains, and mechanical linkages of switch gears. Contains modifier for improved adherence.

GM: 9986113

Lubricant Properties		Typical value	Test Method
Recommended Service Range (°C)		-40 to 125	
Thickener		Lithium Soap	
Base oil	Type	Polyalphaolefin	
	Kinematic viscosity	40°C 100°C	32.6 cSt 5.7 cSt
	Viscosity Index		135
	Flash point	°C	268
	Pouring point	°C	-62
Typical Properties of the Grease		Typical value	Test Method
Color, Appearance		off-white	
Penetration (1/10 mm)	NLGI Grade	2	ASTM D-217
	Unworked	292	ASTM D-217
	Worked	60X 280	ASTM D-217
Oil Separation	24 hour(s)	100°C	2.2
Evaporation	24 hour(s)	100°C	0.1

The typical properties shown on this product data sheet should not be used as a basis for preparing specifications. Refer to our product SDS for detailed safety information on this product. (1504)

Distributed by Newgate Simms Limited

Broughton Mills Road, Bretton, Chester, CH4 0BY, United Kingdom
+44(0)1244 660771 www.newgatesimms.com info@newgatesimms.com